

# (12) United States Patent

## Park et al.

US 9,410,264 B2 (10) **Patent No.:** 

Aug. 9, 2016 (45) Date of Patent:

## (54) INGOT GROWING APPARATUS

(71) Applicant: S-TECH CO., LTD., Daegu (KR)

(72) Inventors: Jin Sub Park, Daegu (KR); Jin No

Kim, Gyeongsangbuk-do (KR); Hyuck

Cheol Kwon, Daegu (KR)

Assignee: S-TECH CO., LTD. (KR)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/897,559

PCT Filed: Apr. 30, 2015

(86) PCT No.: PCT/KR2015/004391

§ 371 (c)(1),

Dec. 10, 2015 (2) Date:

(87) PCT Pub. No.: WO2015/174665

PCT Pub. Date: Nov. 19, 2015

#### (65)**Prior Publication Data**

US 2016/0122898 A1 May 5, 2016

#### (30)Foreign Application Priority Data

May 14, 2014 (KR) ...... 10-2014-0057994

(51) Int. Cl.

C30B 15/20 (2006.01)C30B 15/30 (2006.01)C30B 29/06 (2006.01)

(52) U.S. Cl.

(2013.01); C30B 29/06 (2013.01)

(58) Field of Classification Search

CPC ....... C30B 15/00; C30B 15/20; C30B 15/30;

C30B 35/00; C30B 35/005; Y10T 117/00; Y10T 117/10; Y10T 117/1004; Y10T 117/1008; Y10T 117/1024; Y10T 117/1032; Y10T 117/1056; Y10T 117/1072 USPC ...... 117/200-202, 206, 208, 214, 218 See application file for complete search history.

#### (56)References Cited

## U.S. PATENT DOCUMENTS

## FOREIGN PATENT DOCUMENTS

JP	06-234593	*	8/1994
JP	06234593	A	8/1994
KR	1020010082689	A	8/2001
KR	101155413	B1	6/2011
KR	101153979	B1	6/2012
KR	101159270	B1	6/2012

<sup>\*</sup> cited by examiner

Primary Examiner — Kenneth A Bratland, Jr. (74) Attorney, Agent, or Firm — Levenfeld Pearlstein, LLC

## **ABSTRACT**

An ingot growing apparatus. A main chamber includes a crucible accommodating a source material therein and a heater melting the source material by heating the crucible. A dome chamber is disposed on top of the crucible. A pull chamber is disposed on top of the dome chamber. An ingot grown in the crucible moves via a seed cable within the dome chamber and the pull chamber. A weight-measuring unit is disposed on top of the pull chamber. The weight-measuring unit includes a housing disposed on top of the pull chamber, with the interior thereof being maintained in a vacuum state, a support roller disposed within the housing to support the seed cable, and a load cell disposed outside of the housing to measure a weight of the ingot supported by the support roller.

## 7 Claims, 3 Drawing Sheets

